1 Identification of substance

· Product details

· Trade name: 39141-LV; 39144-LV Trim Black

· Article number: 39141-LV, 39144-LV

· Manufacturer/Supplier: SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730

803 207 8225

· Information department:

cust_care@semproducts.com : SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency information: 24 HR EMERGENCY CHEMTREC 1-800-424-9300

2 Composition/Data on components

- · Chemical characterization
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous	components:	
67-64-1	acetone Danger:	30 - 40%
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene Warning: 1.6/3; 1.3/2A, 3.8/3	30 - 40%
	ACRYLIC RESIN Warning: ① 3.2/2, 3.3/2A, 3.8/3	13 - 30%
123-86-4	n-butyl acetate Warning: 🕎 2.6/3; 🕩 3.8/3	5 - 7%
16883-83-3	benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate Warning: ① 3.2/2, 3.3/2A, 3.8/3	1.5 - 5%
108-88-3	toluene Danger: ② 2.6/2; ③ 3.10/1, 3.7/2, 3.9/2 Warning: ① 3.2/2, 3.8/3	1.5 - 5%
1330-20-7	xylene Warning: (4) 2.6/3; (1) 3.1.D/4, 3.1.I/4, 3.2/2	1.5 - 5%
1333-86-4	Carbon black Warning:	1-1.5%
67-56-1	methanol Danger: (4) 2.6/2; (4) 3.1.0/3, 3.1.D/3, 3.1.I/3; (4) 3.8/1	≤1%

3 Hazards identification

· Hazard description:





Irritant Highly flammable

(Contd. on page 2)

Trade name: 39141-LV; 39144-LV Trim Black

(Contd. of page 1)

· Information pertaining to particular dangers for man and environment:

The product has to be labelled due to the calculation procedure of international guidelines.

Has a narcotizing effect.

Highly flammable.

Irritating to eyes, respiratory system and skin.

Vapours may cause drowsiness and dizziness.

· Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

· NFPA ratings (scale 0 - 4)



Health = 1Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



*1 Health = *1Fire = 3

GHS label elements



2.6/2 - Highly flammable liquid and vapour.



Warning

3.2/2 - Causes skin irritation.

3.3/2A - Causes serious eye irritation.

3.8/3 - May cause respiratory irritation. May cause drowsiness or dizziness.

· Prevention:

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

· Response:

IF ON SKIN: Wash with plenty of soap and water.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a POISON CENTER or doctor/physician if you feel unwell.

Specific treatment (see on this label).

If skin irritation occurs: Get medical advice/attention.

(Contd. on page 3)

Trade name: 39141-LV; 39144-LV Trim Black

(Contd. of page 2)

If eye irritation persists: Get medical advice/attention.

Take off contaminated clothing and wash before reuse.

In case of fire: Use for extinction: CO2, powder or water spray.

· Storage:

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

· Disposal:

Dispose of contents/container in accordance with local/regional/national/international regulations.

4 First aid measures

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: If symptoms persist consult doctor.

5 Fire fighting measures

- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
- · Measures for environmental protection: Do not allow to enter sewers/ surface or ground water.
- · Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

7 Handling and storage

- · Handling:
- · Information for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

(Contd. on page 4)

Trade name: 39141-LV; 39144-LV Trim Black

Store in cool, dry conditions in well sealed receptacles.

(Contd. of page 3)

8 Exposure controls and personal protection

· Addi	ional information about design of technical systems: No further data; see item 7.	
· Components with limit values that require monitoring at the workplace:		
67-64	1-1 acetone	
PEL	2400 mg/m³, 1000 ppm	
	590 mg/m³, 250 ppm	
TLV	Short-term value: 1782 mg/m³, 750 ppm	
	Long-term value: 1188 mg/m³, 500 ppm	
	BEI	
	86-4 n-butyl acetate	
	710 mg/m^3 , 150 ppm	
REL	Short-term value: 950 mg/m³, 200 ppm	
TOTAL	Long-term value: 710 mg/m³, 150 ppm	
ILV	Short-term value: 950 mg/m³, 200 ppm	
100	Long-term value: 713 mg/m³, 150 ppm	
	88-3 toluene	
PEL	Short-term value: C 300; 500* ppm	
	Long-term value: 200 ppm	
DEI	*10-min peak per 8-hr shift Short-term value: 560 mg/m³, 150 ppm	
KEL	Long-term value: 375 mg/m³, 100 ppm	
TLV	75 mg/m^3 , 20 ppm	
	20-7 xylene	
	435 mg/m³, 100 ppm	
	Short-term value: 655 mg/m³, 150 ppm	
	Long-term value: 435 mg/m³, 100 ppm	
TLV	Short-term value: 651 mg/m³, 150 ppm	
	Long-term value: 434 mg/m³, 100 ppm	
	BEI	
	-86-4 Carbon black	
	3.5 mg/m^3	
REL	$3.5* mg/m^3$	
TOTAL	*0.1 in presence of PAHs, as PAHs; 10-hr TWA	
	3.5 mg/m ³	
	í-1 methanol	
	260 mg/m³, 200 ppm	
REL	Short-term value: 325 mg/m³, 250 ppm	
	Long-term value: 260 mg/m³, 200 ppm Skin	
TIV	Skin Short-term value: 328 mg/m³, 250 ppm	
ILV	Snort-term value: 328 mg/m², 230 ppm Long-term value: 262 mg/m³, 200 ppm	
	Skin; BEI	
	, 2	

· Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 5)

Trade name: 39141-LV; 39144-LV Trim Black

(Contd. of page 4)

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· General Information	
Form: Color:	Liquid According to product specification
Odor: Change in condition Melting point/Melting range:	
Boiling point/Boiling range: Flash point:	-4°C (25°F)
· Ignition temperature: · Auto igniting:	370°C (698°F) Product is not selfigniting.
Danger of explosion: Explosion limits:	In use, may form flammable/explosive vapour-air mixture.
	2.6 Vol %

(Contd. on page 6)

Trade name: 39141-LV; 39144-LV Trim Black

(Contd. of page 5)

Upper: 13.0 Vol % · Vapor pressure at 20°C (68°F): 233 hPa (175 mm Hg) · Density at 20°C (68°F): 1.012 g/cm^3 · Solubility in / Miscibility with Water: Not miscible or difficult to mix. · Solvent content: Organic solvents: 75.9 % **VOC** content: 10.4 % 334.0 g/l / 2.79 lb/gl 24.1 % · Solids content:

10 Stability and reactivity

- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Dangerous reactions No dangerous reactions known.
- · Dangerous products of decomposition: No dangerous decomposition products known.

11 Toxicological information

- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

12 Ecological information

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations

- · Product:
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

heet SEM

Printing date 03/10/2010 Reviewed on 03/10/2010

Trade name: 39141-LV; 39144-LV Trim Black

(Contd. of page 6)

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· DOT regulations:



· Hazard class:

· Identification number: UN1263
· Packing group: II
· Proper shipping name (technical name): PAINT
· Label 3

• **Remarks** ORM-D 49CFR 173.150,156,or306

· Land transport TDG (Canada) and ADR/RID (Europe):



· Hazard class: 3 Flammable liquids

 · UN-Number:
 1263

 · Packaging group:
 II

 · Label:
 3

• **Description of goods:** 1263 PAINT, special provision 640D

· Maritime transport IMDG:



IMDG Class:
UN Number:
Label
Packaging group:
EMS Number:
Marine pollutant:
Propper shipping name:

· Air transport ICAO-TI and IATA-DGR:



· ICAO/IATA Class: 3 *· UN/ID Number:* 1263 *· Label* 3

(Contd. on page 8)

Trade name: 39141-LV; 39144-LV Trim Black

(Contd. of page 7)

Packaging group: II
 Propper shipping name: PAINT

· UN "Model Regulation": UN1263, PAINT, 3, II

15 Regulations

· Sara

	· Section 355	(extremely	v hazardous	substances):
--	---------------	------------	-------------	--------------

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

\ 1 J		
	ACRYLIC RESIN	
108-88-3	toluene	

1330-20-7 xylene

100-41-4 ethylbenzene

67-56-1 methanol

· TSCA (Toxic Substances Control Act):

67-64-1	acetone

98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene

123-86-4 n-butyl acetate

16883-83-3 benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate

108-88-3 toluene

1330-20-7 xylene

1333-86-4 Carbon black

68611-44-9 Silane Modified Silica

111-76-2 2-butoxyethanol

68855-54-9 Kieselguhr, soda ash flux-calcined

68911-87-5 ALKYL QUATERNARY AMMONIUM MONTMORILLONITE

9002-88-4 *POLYETHYLENE*

100-41-4 ethylbenzene

67-56-1 methanol

7732-18-5 water, distilled, conductivity or of similar purity

· Proposition 65

· Chemicals known to cause cancer:

1330-20-7 xylene

1333-86-4 Carbon black

68855-54-9 Kieselguhr, soda ash flux-calcined

68911-87-5 ALKYL QUATERNARY AMMONIUM MONTMORILLONITE

100-41-4 ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

(Contd. on page 9)

Trade name: 39141-LV; 39144-LV Trim Black

(Contd. of page 8) · Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. · Chemicals known to cause developmental toxicity: 108-88-3 toluene · Cancerogenity categories · EPA (Environmental Protection Agency) 67-64-1 acetone 108-88-3 toluene II 1330-20-7 xylene 111-76-2 2-butoxyethanol CBD100-41-4 ethylbenzene D · IARC (International Agency for Research on Cancer) 108-88-3 toluene 3 1330-20-7 xylene 3 1333-86-4 Carbon black 2B111-76-2 2-butoxyethanol 3 68855-54-9 Kieselguhr, soda ash flux-calcined GROUP 1 9002-88-4 *POLYETHYLENE* 3 100-41-4 ethylbenzene 2*B* · NTP (National Toxicology Program) 68855-54-9 Kieselguhr, soda ash flux-calcined HUMAN CARCINOGEN · TLV (Threshold Limit Value established by ACGIH) 67-64-1 acetone A4 108-88-3 toluene A41330-20-7 xylene *A4* 1333-86-4 Carbon black *A4* 111-76-2 2-butoxyethanol *A3* 100-41-4 ethylbenzene *A3* · NIOSH-Ca (National Institute for Occupational Safety and Health) 1333-86-4 Carbon black 67-56-1 methanol · OSHA-Ca (Occupational Safety & Health Administration) 68911-87-5 ALKYL QUATERNARY AMMONIUM MONTMORILLONITE

· Product related hazard informations:

The product has been classified and marked in accordance with directives on hazardous materials.

· Hazard symbols:

Irritant

Highly flammable

· Risk phrases:

Highly flammable.

Irritating to eyes, respiratory system and skin.

Vapours may cause drowsiness and dizziness.

(Contd. on page 10)

Trade name: 39141-LV; 39144-LV Trim Black

(Contd. of page 9)

· Safety phrases:

Keep in a cool place.

Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).

Use only in well-ventilated areas.

This material and its container must be disposed of as hazardous waste.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing MSDS: Environment protection department.
- · Contact: Steve Gaver
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

USA