



## 1 Identification of substance

- **Product details**
- **Trade name:** 39387 Self Leveling Seam Sealer
- **Article number:** 39387
- **Manufacturer/Supplier:**  
SEM Products, Inc.  
651 Michael Wylie Dr.  
Charlotte, NC 28217  
USA  
(704)522-1006
- **Information department:** 24HR EMERGENCY CHEMTREC 800-424-9300

## 2 Composition/Data on components

- **Chemical characterization**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

	MERCAPTAN TERMINATED POLYMER	25-50%
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)	25-50%
1317-65-3	GROUND CALCIUM CARBONATE	10-25%
26142-30-3	POLYMER OF EPICHLOROHYDRIN-POLYGLYCOL	2.5-10%
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	≤ 2.5%
17557-23-2	1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane	≤ 2.5%
67762-90-7	FUMED SILICA	≤ 2.5%
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	≤ 2.5%

## 3 Hazards identification

- **Hazard description:**



Harmful  
Dangerous for the environment

- **Information pertaining to particular dangers for man and environment:**

The product has to be labelled due to the calculation procedure of international guidelines.

Harmful by inhalation, in contact with skin and if swallowed.

Irritating to eyes, respiratory system and skin.

May cause sensitisation by skin contact.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Contains epoxy constituents. See information supplied by the manufacturer.

- **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- **NFPA ratings (scale 0 - 4)**



Health = 2  
Fire = 1  
Reactivity = 0

(Contd. on page 2)

Trade name: 39387 Self Leveling Seam Sealer

(Contd. of page 1)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = 2
FIRE	1	Fire = 1
REACTIVITY	0	Reactivity = 0

#### 4 First aid measures

· **General information:**

*Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.*

· **After inhalation:**

*Supply fresh air and to be sure call for a doctor.*

*In case of unconsciousness place patient stably in side position for transportation.*

· **After skin contact:** *Immediately wash with water and soap and rinse thoroughly.*

· **After eye contact:**

*Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.*

· **After swallowing:** *Immediately call a doctor.*

#### 5 Fire fighting measures

· **Suitable extinguishing agents:**

*CO<sub>2</sub>, sand, extinguishing powder. Do not use water.*

*Use fire fighting measures that suit the environment.*

· **For safety reasons unsuitable extinguishing agents:** *Water*

· **Protective equipment:** *Mouth respiratory protective device.*

#### 6 Accidental release measures

· **Person-related safety precautions:** *Not required.*

· **Measures for environmental protection:**

*Do not allow product to reach sewage system or any water course.*

*Inform respective authorities in case of seepage into water course or sewage system.*

*Do not allow to enter sewers/ surface or ground water.*

· **Measures for cleaning/collecting:**

*Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).*

*Dispose contaminated material as waste according to item 13.*

*Ensure adequate ventilation.*

*Do not flush with water or aqueous cleansing agents*

#### 7 Handling and storage

· **Handling:**

· **Information for safe handling:**

*Ensure good ventilation/exhaustion at the workplace.*

*Prevent formation of aerosols.*

· **Information about protection against explosions and fires:** *No special measures required.*

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** *No special requirements.*

· **Information about storage in one common storage facility:** *Not required.*

(Contd. on page 3)



**Trade name: 39387 Self Leveling Seam Sealer**

(Contd. of page 2)

· **Further information about storage conditions:** Keep receptacle tightly sealed.

## 8 Exposure controls and personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Components with limit values that require monitoring at the workplace:**

### 1317-65-3 GROUND CALCIUM CARBONATE

PEL	15*; 5** mg/m <sup>3</sup> *Total dust **Respirable fraction
REL	10*; 5** mg/m <sup>3</sup> *Total dust **Respirable fraction
TLV	10 mg/m <sup>3</sup> (e)

### 67762-90-7 FUMED SILICA

TLV	Short-term value: 10 mg/m <sup>3</sup>
-----	--

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles



**Trade name: 39387 Self Leveling Seam Sealer**

(Contd. of page 3)

## 9 Physical and chemical properties

### · General Information

<b>Form:</b>	Fluid
<b>Color:</b>	According to product specification
<b>Odor:</b>	Characteristic

### · Change in condition

**Melting point/Melting range:** Undetermined.  
**Boiling point/Boiling range:** 201°C (394°F)

· **Flash point:** 257°C (495°F)

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Density at 20°C (68°F):** 1.23 g/cm<sup>3</sup>

· **Solubility in / Miscibility with Water:** Not miscible or difficult to mix.

### · Solvent content:

**Organic solvents:** 0.0 %  
**VOC content:** 1.5 g/l / 0.01 lb/gl

· **Solids content:** 99.9 %

## 10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous products of decomposition:** No dangerous decomposition products known.

## 11 Toxicological information

- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Harmful  
Irritant

## 12 Ecological information

- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **General notes:**  
Water hazard class 2 (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Also poisonous for fish and plankton in water bodies.

(Contd. on page 5)

Trade name: 39387 Self Leveling Seam Sealer

Toxic for aquatic organisms

(Contd. of page 4)

### 13 Disposal considerations

- **Product:**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

· **DOT regulations:**

· **Label** ADHESIVE NON HAZARDOUS

· **Land transport ADR/RID (cross-border):**



- **ADR/RID class:** 6.1 Toxic substances
- **Danger code (Kemler):** 60
- **UN-Number:** 2810
- **Packaging group:** III
- **Label:** 6.1
- **Description of goods:** 2810 TOXIC LIQUID, ORGANIC, N.O.S. (MERCAPTAN TERMINATED POLYMER, GROUND CALCIUM CARBONATE)

· **Maritime transport IMDG:**



- **IMDG Class:** 6.1
- **UN Number:** 2810
- **Label** 6.1
- **Packaging group:** III
- **EMS Number:** F-A,S-A
- **Marine pollutant:** No
- **Propper shipping name:** TOXIC LIQUID, ORGANIC, N.O.S. (MERCAPTAN TERMINATED POLYMER, GROUND CALCIUM CARBONATE)

(Contd. on page 6)

Trade name: 39387 Self Leveling Seam Sealer

(Contd. of page 5)

· Air transport ICAO-TI and IATA-DGR:



- ICAO/IATA Class: 6.1
- UN/ID Number: 2810
- Label: 6.1
- Packaging group: III
- Propper shipping name: TOXIC LIQUID, ORGANIC, N.O.S. (MERCAPTAN TERMINATED POLYMER, GROUND CALCIUM CARBONATE)

## 15 Regulations

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

68909-14-8 ELASTOMER MODIFIED DIGLYCIDAL ETHER

107-21-1 ethanediol

67-56-1 methanol

· TSCA (Toxic Substances Control Act):

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

90-72-2 2,4,6-tris(dimethylaminomethyl)phenol

17557-23-2 1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane

919-30-2 3-aminopropyltriethoxysilane

2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane

13463-67-7 titanium dioxide

107-21-1 ethanediol

14808-60-7 Quartz (SiO<sub>2</sub>)

7732-18-5 water, distilled, conductivity or of similar purity

1333-86-4 Carbon black

64-17-5 ethanol

67-56-1 methanol

· Proposition 65

· Chemicals known to cause cancer:

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

74398-71-3 CASTOR OIL GLYCIDAL ETHER

14808-60-7 Quartz (SiO<sub>2</sub>)

1333-86-4 Carbon black

· Chemicals known to cause reproductive toxicity:

74398-71-3 CASTOR OIL GLYCIDAL ETHER

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

(Contd. on page 7)



**Trade name: 39387 Self Leveling Seam Sealer**

(Contd. of page 6)

<b>· IARC (International Agency for Research on Cancer)</b>		
13463-67-7	titanium dioxide	3
14808-60-7	Quartz (SiO <sub>2</sub> )	1
1333-86-4	Carbon black	2B
<b>· NTP (National Toxicology Program)</b>		
14808-60-7	Quartz (SiO <sub>2</sub> )	K
<b>· TLV (Threshold Limit Value established by ACGIH)</b>		
13463-67-7	titanium dioxide	A4
107-21-1	ethanediol	A4
14808-60-7	Quartz (SiO <sub>2</sub> )	A2
1333-86-4	Carbon black	A4
64-17-5	ethanol	A4
<b>· NIOSH-Ca (National Institute for Occupational Safety and Health)</b>		
13463-67-7	titanium dioxide	
14808-60-7	Quartz (SiO <sub>2</sub> )	
1333-86-4	Carbon black	
<b>· OSHA-Ca (Occupational Safety &amp; Health Administration)</b>		
None of the ingredients is listed.		

**· Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

**· Hazard symbols:**

Harmful

Dangerous for the environment

**· Hazard-determining components of labelling:**

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane

MERCAPTAN TERMINATED POLYMER

**· Risk phrases:**

Harmful by inhalation, in contact with skin and if swallowed.

Irritating to eyes, respiratory system and skin.

May cause sensitisation by skin contact.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**· Safety phrases:**

Keep out of the reach of children.

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

Wear suitable protective clothing, gloves and eye/face protection.

If swallowed, seek medical advice immediately and show this container or label.

**· Special labeling of certain preparations:**

Contains epoxy constituents. See information supplied by the manufacturer.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing MSDS:** Environment protection department.

· **Contact:** Mr. George Wallace