1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: 40482 Bumper Bite Flexible Glaze (w/HRDNR)
- · Article number: 40482
- · Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the preparation coating
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SEM Products Inc. 1685 Overview Drive

Rock Hill, SC 29730

803 207 8225

· Information department:

cust_care@semproducts.com : SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency telephone number: 24 HR EMERGENCY CHEMTREC 1-800-424-9300

2 Hazards identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



Skin Irrit. 2 H315 Causes skin irritation.

H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

Acute Tox. 5 H333 May be harmful if inhaled.

- · Label elements
- · GHS label elements The product is classified and labelled according to the Globally Harmonized System (GHS).
- · Hazard pictograms GHS02, GHS07
- · Signal word Warning
- · Hazard statements

H226 Flammable liquid and vapour.

H333 May be harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 2)

Trade name: 40482 Bumper Bite Flexible Glaze (w/HRDNR)

(Contd. of page 1)

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2Fire = 3

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable. · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description**: Mixture of the substances listed below with nonhazardous additions.

· Dangerous	components:	
14807-96-6	Talc	30 - 40%
	♦ Skin Irrit. 2, H315; H319; STOT SE 3, H335	
100-42-5	styrene	13 - 30%
	🚸 Flam. Liq. 3, H226; 산 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	
65997-17-3	Glass	7 - 10%
	♦ Skin Irrit. 2, H315; H319; STOT SE 3, H335	
	POLYESTER RESIN	5 - 7%
	♦ Skin Irrit. 2, H315; H319; STOT SE 3, H335	

4 First aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)

Trade name: 40482 Bumper Bite Flexible Glaze (w/HRDNR)

(Contd. of page 2)

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Dilute with plenty of water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

USA ·

Trade name: 40482 Bumper Bite Flexible Glaze (w/HRDNR)

(Contd. of page 3)

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

100-42-5 styrene

PEL Short-term value: C 200; 600* ppm

Long-term value: 100 ppm *5-min peak in any 3 hrs

REL Short-term value: 425 mg/m³, 100 ppm Long-term value: 215 mg/m³, 50 ppm TLV Short-term value: 170 mg/m³, 40 ppm Long-term value: 85 mg/m³, 20 ppm

BEI

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/the substance/the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

-US/

Trade name: 40482 Bumper Bite Flexible Glaze (w/HRDNR)

(Contd. of page 4)

Physical and chemical propert			
Information on basic physical and cl	hemical properties		
General Information Appearance:			
Form:	Liquid		
Color:	According to product specification		
· Odor:	Characteristic		
Odour threshold:	Not determined.		
pH-value:	Not determined.		
Change in condition			
Melting point/Melting range:	Undetermined.		
Boiling point/Boiling range:	145°C		
Flash point:	31°C		
Flammability (solid, gaseous):	Not applicable.		
· Ignition temperature:	480°C		
Decomposition temperature:	Not determined.		
Auto igniting:	Product is not selfigniting.		
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.		
Explosion limits:			
Lower:	1.2 Vol %		
Upper:	8.9 Vol %		
Vapor pressure at 20°C:	8 hPa		
Density at 20°C:	1.62 g/cm ³		
Relative density	Not determined.		
Vapour density	Not determined.		
Evaporation rate	Not determined.		
Solubility in / Miscibility with			
Water:	Fully miscible.		
Segregation coefficient (n-octonol/w	ater): Not determined.		
Viscosity:			
Dynamic:	Not determined.		
Kinematic:	Not determined.		
Solvent content:			
Organic solvents:	0.0 %		
Solids content:	100.0 %		
Other information	No further relevant information available.		

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 6)

Trade name: 40482 Bumper Bite Flexible Glaze (w/HRDNR)

(Contd. of page 5)

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

100-42-5 styrene

 Oral
 LD50
 5000 mg/kg (rat)

 Inhalative
 LC50/4 h
 24 mg/l (rat)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Generally not hazardous for water
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · **Recommendation**: Disposal must be made according to official regulations.
- · **Recommended cleansing agent:** Water, if necessary with cleansing agents.

USA

(Contd. on page 7)

Trade name: 40482 Bumper Bite Flexible Glaze (w/HRDNR)

(Contd. of page 6)

TINI NI I			
UN-Number DOT, ADR, IMDG, IATA	UN2055		
UN proper shipping name DOT, IMDG, IATA ADR	STYRENE MONOMER, STABILIZED, mixture 2055 STYRENE MONOMER, STABILIZED, mixture		
Transport hazard class(es)			
DOT			
FLAMMARIE LOUIS			
Class	3 Flammable liquids.		
Label	3		
Class	3 Flammable liquids		
Label	3		
Packing group DOT, ADR, IMDG, IATA	III		
Environmental hazards: Marine pollutant:	No		
Special precautions for user EMS Number:	Warning: Flammable liquids F-E,S-D		
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.		
UN "Model Regulation":	UN2055, STYRENE MONOMER, STABILIZED, mixture, 3, III		

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

· Section 355	(extremely	hazardou	s substances):
---------------	------------	----------	----------------

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

14807-96-6 Talc 100-42-5 styrene

(Contd. on page 8)

Trade name: 40482 Bumper Bite Flexible Glaze (w/HRDNR)

(Contd. of page 7) · TSCA (Toxic Substances Control Act): 14807-96-6 Talc 26123-45-5 1,3-ISOBENZOFURANDIONE,POLYMER WITH 2,5-FURANDIONE AND 2,2-OXYBIS **ETHANOL** 100-42-5 styrene 65997-17-3 Glass 13463-67-7 titanium dioxide 7631-86-9 silicon dioxide, chemically prepared 21645-51-2 aluminium hydroxide · Proposition 65 · Chemicals known to cause cancer: None of the ingredients is listed. · Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed. · Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. · Chemicals known to cause developmental toxicity: None of the ingredients is listed. · Cancerogenity categories · EPA (Environmental Protection Agency) None of the ingredients is listed. · TLV (Threshold Limit Value established by ACGIH) 14807-96-6 Talc A4100-42-5 styrene A413463-67-7 titanium dioxide A4· NIOSH-Ca (National Institute for Occupational Safety and Health) 13463-67-7 titanium dioxide · OSHA-Ca (Occupational Safety & Health Administration) None of the ingredients is listed.

- · GHS label elements The product is classified and labelled according to the Globally Harmonized System (GHS).
- · Hazard pictograms GHS02, GHS07
- · Signal word Warning
- · Hazard statements

H226 Flammable liquid and vapour.

H333 May be harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 9)

Trade name: 40482 Bumper Bite Flexible Glaze (w/HRDNR)

(Contd. of page 8)

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing MSDS: Environment protection department.
- · Contact: Steve Gaver
- · Abbreviations and acronyms:

ICAO: International Civil Aviation Organization

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

-USA