



1 Identification of the substance/mixture and of the company/undertaking

· Product details

· Trade name: **40524 Low VOC Rubberized Undercoating**

· Article number: 40524

· Application of the substance / the preparation coating

· Manufacturer/Supplier:

SEM Products Inc.
1685 Overview Drive
Rock Hill, SC 29730
803 207 8225

· Information department:

cust_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency information: 24 HR EMERGENCY CHEMTREC 1-800-424-9300

2 Composition/information on ingredients

· Chemical characterization

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene H226; H315; H319; H335	30 - 40%
64742-89-8	Solvent naphtha (petroleum), light aliph. H340; H350; H304	13 - 30%
69430-35-9	Alicyclic hydrocarbon resin H315; H319; H335	7 - 10%
9017-27-0	Alpha-methyl styrene/vinyl toluene copolymer H315; H319; H335	7 - 10%
14807-96-6	Talc (Mg3H2(SiO3)4) H315; H319; H335	7 - 10%
66070-58-4	Styrene-Ethylene/Butylene-Styrene block Copolymer H315; H319; H335	5 - 7%

3 Hazards identification

· Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008



GHS02 Flame

H225 Highly flammable liquid and vapour.



GHS08 Health hazard

H340 May cause genetic defects.

H350 May cause cancer.

(Contd. on page 2)



Trade name: 40524 Low VOC Rubberized Undercoating

(Contd. of page 1)



GHS07

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC


Toxic

May cause cancer. May cause heritable genetic damage.



Irritant

Irritating to eyes, respiratory system and skin.



Highly flammable

Highly flammable.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of international guidelines.

Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

Label elements
Labelling according to Regulation (EC) No 1272/2008
Hazard pictograms


GHS02



GHS07



GHS08

Signal word Danger
Hazard-determining components of labelling:
Solvent naphtha (petroleum), light aliph.
methanol
Hazard statements

Highly flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

May cause genetic defects.

May cause cancer.

May cause respiratory irritation.

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

Trade name: 40524 Low VOC Rubberized Undercoating

(Contd. of page 2)

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with directives on hazardous materials.

· **Code letter and hazard designation of product:**



Toxic
Highly flammable

· **Hazard-determining components of labelling:**

Solvent naphtha (petroleum), light aliph.

· **Risk phrases:**

May cause cancer.

May cause heritable genetic damage.

Highly flammable.

Irritating to eyes, respiratory system and skin.

· **Safety phrases:**

Avoid exposure - obtain special instructions before use.

Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).

In case of insufficient ventilation, wear suitable respiratory equipment.

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

This material and its container must be disposed of as hazardous waste.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = *1

Fire = 3

Reactivity = 0

4 First aid measures

· **After inhalation:** *In case of unconsciousness place patient stably in side position for transportation.*

· **After skin contact:** *Immediately wash with water and soap and rinse thoroughly.*

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** *If symptoms persist consult doctor.*

5 Firefighting measures

· **Suitable extinguishing agents:** *CO₂, sand, extinguishing powder. Do not use water.*

· **For safety reasons unsuitable extinguishing agents:** *Water with full jet*

(Contd. on page 4)



Printing date 04/22/2011

Reviewed on 04/22/2011

Trade name: 40524 Low VOC Rubberized Undercoating

(Contd. of page 3)

· **Protective equipment:** No special measures required.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:** Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
 - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 - Dispose contaminated material as waste according to item 13.
 - Ensure adequate ventilation.
 - Do not flush with water or aqueous cleansing agents

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
 - No special measures required.
 - Ensure good ventilation/exhaustion at the workplace.
 - Open and handle receptacle with care.
 - Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
 - Keep respiratory protective device available.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 - Keep receptacle tightly sealed.
 - Store in cool, dry conditions in well sealed receptacles.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Components with limit values that require monitoring at the workplace:**
 - The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during the creation were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all soiled and contaminated clothing.
 - Wash hands before breaks and at the end of work.
 - Store protective clothing separately.
 - Avoid contact with the eyes and skin.
- **Breathing equipment:**
 - In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 5)


Trade name: 40524 Low VOC Rubberized Undercoating

(Contd. of page 4)

· Protection of hands:


Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:


Tightly sealed goggles

9 Physical and chemical properties
· General Information
· Appearance:

Form: Liquid
Color: According to product specification
· Odor: Characteristic

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 139°C (282°F)

· Flash point: 10°C (50°F)

· Ignition temperature: 455°C (851°F)

· Auto igniting: Product is not selfigniting.

· Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

· Explosion limits:

Lower: 1.2 Vol %
Upper: 16.0 Vol %

· Vapor pressure at 20°C (68°F): 14 hPa (11 mm Hg)

· Density at 20°C (68°F): 1.0461 g/cm³ (8.73 lbs/gal)

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

(Contd. on page 6)



Printing date 04/22/2011

Reviewed on 04/22/2011

Trade name: 40524 Low VOC Rubberized Undercoating

(Contd. of page 5)

- | | |
|----------------------------------|-------------------------|
| · Viscosity: | |
| Kinematic at 20°C (68°F): | 100 s (DIN 53211/4) |
| · Solvent content: | |
| Organic solvents: | 30.1 % |
| VOC content: | 30.0 % |
| | 421.6 g/l / 3.52 lb/gal |
| · Solids content: | |
| | 69.9 % |

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Materials to be avoided:**
- **Dangerous reactions:** No dangerous reactions known.
- **Dangerous products of decomposition:** No dangerous decomposition products known.

11 Toxicological information

- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
Carcinogenic.
The product can cause inheritable damage.

12 Ecological information

- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations

- **Product:**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

USA



Printing date 04/22/2011

Reviewed on 04/22/2011

Trade name: 40524 Low VOC Rubberized Undercoating

(Contd. of page 6)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· DOT regulations:



- **Hazard class:** 3
- **Identification number:** UN1263
- **Packing group:** III
- **Proper shipping name (technical name):** PAINT
- **Label:** 3
- **Remarks:** ORM-D 49CFR 173.150,156,306

· Land transport TDG (Canada) and ADR/RID (Europe):



- **Hazard class:** 3 Flammable liquids
- **UN-Number:** 1263
- **Packaging group:** III
- **Label:** 3
- **Description of goods:** 1263 PAINT, special provision 640H

· Maritime transport IMDG:



- **IMDG Class:** 3
- **UN Number:** 1263
- **Label:** 3
- **Packaging group:** III
- **EMS Number:** F-E,S-E
- **Marine pollutant:** No
- **Propper shipping name:** PAINT

· Air transport ICAO-TI and IATA-DGR:



- **ICAO/IATA Class:** 3
- **UN/ID Number:** 1263
- **Label:** 3

(Contd. on page 8)

USA



Printing date 04/22/2011

Reviewed on 04/22/2011

Trade name: 40524 Low VOC Rubberized Undercoating

(Contd. of page 7)

- **Packaging group:** III
- **Propper shipping name:** PAINT
- **UN "Model Regulation":** UN1263, PAINT, 3, III

15 Regulatory information

· Sara

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

14807-96-6 Talc ($Mg_3H_2(SiO_3)_4$)

67-56-1 methanol

· **TSCA (Toxic Substances Control Act):**

98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene

64742-89-8 Solvent naphtha (petroleum), light aliph.

69430-35-9 Alicyclic hydrocarbon resin

9017-27-0 Alpha-methyl styrene/vinyl toluene copolymer

14807-96-6 Talc ($Mg_3H_2(SiO_3)_4$)

66070-58-4 Styrene-Ethylene/Butylene-Styrene block Copolymer

1333-86-4 Carbon black

8042-47-5 White Mineral oil

6683-19-8 Tertrakis(methylene(3,5-di(tert)-butyl-4-hydroxyhydrocinnamate)) methane

67-56-1 methanol

· **Proposition 65**

· **Chemicals known to cause cancer:**

1333-86-4 Carbon black

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogeny categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **IARC (International Agency for Research on Cancer)**

14807-96-6 Talc ($Mg_3H_2(SiO_3)_4$)

3

1333-86-4 Carbon black

2B

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

(Contd. on page 9)

USA



Printing date 04/22/2011

Reviewed on 04/22/2011

Trade name: 40524 Low VOC Rubberized Undercoating

(Contd. of page 8)

· TLV (Threshold Limit Value established by ACGIH)

14807-96-6	Talc ($Mg_3H_2(SiO_3)_4$)	A4
1333-86-4	Carbon black	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

1333-86-4	Carbon black
67-56-1	methanol

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

· Chemical safety assessment A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing MSDS: Environment protection department.

· Contact: Steve Gaver

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

USA