

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/05/2011

Revised On 01/05/2011

1 Identification of the substance and manufacturer

Trade name: SPRUCE GLOSS BLACK LACQUER
Product code: 0000980018
Manufacturer/Supplier: SEYMOUR OF SYCAMORE
 917 Crosby Avenue
 Sycamore, IL 60178
 (815)-895-9101, www.seymourpaint.com
Emergency telephone number: CHEMTEL 1-800-255-3924, 813-248-0585 *if located outside the U.S.*



2 Composition/information on ingredients

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

67-64-1	Acetone	30.72%
74-98-6	propane	13.91%
108-10-1	methyl isobutyl ketone	13.38%
106-97-8	n-butane	8.17%
108-88-3	Toluene	4.09%
64-17-5	ethyl alcohol	3.86%
78-93-3	methyl ethyl ketone	3.81%
111-76-2	Glycol Ether EB	3.33%
108-21-4	isopropyl acetate	3.08%
67-63-0	isopropyl alcohol	2.08%
77-90-7	Acetyl Tributyl Citrate	1.89%

3 Hazards identification

Hazard Information: Extremely flammable liquid and vapor. Keep away from heat, sparks, and flame.
 Has narcotizing effect.

Risk phrases: Extremely flammable.
 Irritating to eyes.
 Vapours may cause drowsiness and dizziness

Safety phrases: Keep out of the reach of children.
 Keep away from sources of ignition - No smoking.
 Do not breathe gas/fumes/vapour/spray.
 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point
 If swallowed, seek medical advice immediately and show this container or label.
 Use only in well-ventilated areas.

Special precautions: Do not spray on a naked flame or any incandescent material.
 Buildup of explosive mixtures possible without sufficient ventilation.

Effects of chronic overexposure: May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

NFPA ratings (0 - 4): Health = 1
 Fire = 4
 Reactivity = 3

HMS-ratings (0 - 4): Health= 1
 Fire= 4
 Physical Hazard= 3

4 First aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact: Move to fresh air. Rinse opened eye for several minutes under running water.
After swallowing: Contact physician or poison control center.

5 Firefighting measures

Extinguishing agents: CO2, sand, extinguishing powder, or water spray.
Special hazards: No further relevant information available.
Protective equipment: No special measures required.

6 Accidental release measures

Personal safety procedures: Wear protective equipment. Keep unprotected persons away.
Environmental precautions: Do not allow product to reach sewage systems or ground water.
Additional precautions: Ensure adequate ventilation.

7 Handling and storage

Fire/explosion protection: Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic discharges.
Storage requirements: Observe pressurized container storage regulations. Consult with your local authorities.

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/05/2011

Revised On 01/05/2011

Trade name: SPRUCE GLOSS BLACK LACQUER

(Contd. of page 1)

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

67-64-1 Acetone

PEL 2400 mg/m³, 1000 ppm
 REL 590 mg/m³, 250 ppm
 TLV Short-term value: 1782 mg/m³, 750 ppm
 Long-term value: 1188 mg/m³, 500 ppm
 BEI

74-98-6 propane

PEL 1800 mg/m³, 1000 ppm
 REL 1800 mg/m³, 1000 ppm
 TLV Varies mg/m³, 1000 ppm

108-10-1 methyl isobutyl ketone

PEL 410 mg/m³, 100 ppm
 REL Short-term value: 300 mg/m³, 75 ppm
 Long-term value: 205 mg/m³, 50 ppm
 TLV Short-term value: 307 mg/m³, 75 ppm
 Long-term value: (205) 82 mg/m³, (50) NIC-20 ppm
 (BEI);NIC-A3

106-97-8 n-butane

REL 1900 mg/m³, 800 ppm
 TLV Varies mg/m³, 1000 ppm

108-88-3 Toluene

PEL Short-term value: C 300; 500* ppm
 Long-term value: 200 ppm
 *10-min peak per 8-hr shift
 REL Short-term value: 560 mg/m³, 150 ppm
 Long-term value: 375 mg/m³, 100 ppm
 TLV 75 mg/m³, 20 ppm
 NIC-BEI

64-17-5 ethyl alcohol

PEL 1900 mg/m³, 1000 ppm
 REL 1900 mg/m³, 1000 ppm
 TLV Short-term value: 1880 mg/m³, 1000 ppm

78-93-3 methyl ethyl ketone

PEL 590 mg/m³, 200 ppm
 REL Short-term value: 885 mg/m³, 300 ppm
 Long-term value: 590 mg/m³, 200 ppm
 TLV Short-term value: 885 mg/m³, 300 ppm
 Long-term value: 590 mg/m³, 200 ppm
 BEI

111-76-2 Glycol Ether EB

PEL 240 mg/m³, 50 ppm
 Skin
 REL 24 mg/m³, 5 ppm
 Skin
 TLV 97 mg/m³, 20 ppm
 BEI

108-21-4 isopropyl acetate

PEL 950 mg/m³, 250 ppm
 TLV Short-term value: 836 mg/m³, 200 ppm
 Long-term value: 418 mg/m³, 100 ppm

67-63-0 isopropyl alcohol

PEL 980 mg/m³, 400 ppm
 REL Short-term value: 1225 mg/m³, 500 ppm
 Long-term value: 980 mg/m³, 400 ppm
 TLV Short-term value: 984 mg/m³, 400 ppm
 Long-term value: 492 mg/m³, 200 ppm
 BEI

Hygienic protection:

Keep away from foodstuffs and animal feed. Wash hands after use.

Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection:

Protective gloves. The glove material has to be impermeable and resistant to the substance. No glove recommendation can be given.

Eye protection:

Tightly sealed goggles

9 Physical and chemical properties

Odor: Aromatic

pH-value: Not determined.

Boiling point: -110°C (-166°F)

Flash point: -19°C (-2°F)

Auto igniting: Product is not self-igniting.

Danger of explosion: Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.7 Vol %

Upper Explosion Limit: 10.9 Vol %

(Contd. on page 3)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/05/2011

Revised On 01/05/2011

Trade name: SPRUCE GLOSS BLACK LACQUER

(Contd. of page 2)

Vapor Pressure: 40 PSI, 2750 hPa
Specific Gravity: Between 0.77 and 0.85 (Water equals 1.00)
VOC content: 611.4 g/l / 5.10 lb/gl
VOC content (less exempt solvents): 57.2 %
MIR Value: 1.34
Solids content: 10.2 %
Other information: No further relevant information available.

10 Stability and reactivity

Conditions to avoid: Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.
Hazardous reactions: No dangerous reactions known.
Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

Skin effects: No irritant effect.
Eye effects: Irritating effect.
Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.
Other information: This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), or chlorinated solvents.

13 Disposal considerations

DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.
Recommendation: Completely empty cans should be recycled.

14 Transport information

Hazard class: 2.1
Identification number: N/A
Label: 2.1
ADR/RID/TDG class: 2 5F Gases
UN-Number: 1950
IMDG Class: 2.1
Packaging group: II
EMS Number: F-D,S-U
Marine pollutant: No
ICAO/IATA Class: 2.1
Special marking: Consumer Commodity ORM-D

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-10-1	methyl isobutyl ketone
108-88-3	Toluene
78-93-3	methyl ethyl ketone
111-76-2	Glycol Ether EB
67-63-0	isopropyl alcohol

TSCA: All ingredients are listed.

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

1333-86-4	Carbon black
-----------	--------------

California Proposition 65 chemicals known to cause developmental toxicity:
CANADIAN ENVIRONMENTAL PROTECTION ACT:
WHMIS Symbols for Canada:

108-88-3 Toluene

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

A - Compressed gas
D2B - Toxic material causing other toxic effects



EPA: A= Known human carcinogen B= Probable human carcinogen
 C= Possible human carcinogen
 D= Not classifiable as to human carcinogenicity: Inadequate human and animal evidence of carcinogenicity (or no data is available).
 I: 'Data are inadequate for an assessment of human carcinogen potential.'
 II: 'Inadequate information to assess carcinogenic potential.'

67-64-1	Acetone	I
108-10-1	methyl isobutyl ketone	I
108-88-3	Toluene	II

(Contd. on page 4)
USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/05/2011

Revised On 01/05/2011

Trade name: SPRUCE GLOSS BLACK LACQUER

(Contd. of page 3)

78-93-3	methyl ethyl ketone	1
111-76-2	Glycol Ether EB	CBD

IARC: Group 2A: The ingredient is probably carcinogenic to humans.
 Group 2B: The ingredient is possibly carcinogenic to humans. There is limited evidence of carcinogenicity.
 Group 3: The ingredient is unclassifiable as to its carcinogenicity to humans.

108-88-3	Toluene	3
111-76-2	Glycol Ether EB	3
67-63-0	isopropyl alcohol	3

ACGIH: A1-designates a confirmed human carcinogen.
 A2-designates a suspected human carcinogen.
 A3-designates an animal carcinogen.
 A4-designates "not classifiable as a human carcinogen".

67-64-1	Acetone	A4
108-88-3	Toluene	A4
64-17-5	ethyl alcohol	A3
111-76-2	Glycol Ether EB	A3
67-63-0	isopropyl alcohol	A4

NIOSH: The following substances are regulated in the United States with reference to occupational exposure limits:

1333-86-4	Carbon black
-----------	--------------

Hazard symbols:

Irritant
Extremely flammable

16 Other information

This product was manufactured in the U.S.A.

The information on this sheet is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Contact: Regulatory Affairs

Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 ISO: International Organization for Standardization
 DOT: US Department of Transportation
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 EPA: Environmental Protection Agency
 IARC: International Agency for the Research of Cancer
 NIOSH: National Institute for Occupational Safety and Health
 TSCA: Toxic Substances Control Act
 CPSC: Consumer Product Safety Commission

USA